

19" HD LCD Monitors

LCD-1901HD

LCD-1901HDL

LCD-1901HDR



LCD-1901HDL



LCD-1901HDR



LCD-1901HD

- HD compatible (supports 480p/i, 720p, 1080p/i)
- RS-232 serial control provided
- Underscan capability
- Displays 16:9 and 4:3
- Front controls for Power, Menu, Up/Down, and Select
- On-screen display for brightness, contrast, back light, hue, and volume
- IR remote control
- Composite x 2, S-Video, component, and PC capability
- Active matrix technology allows wide viewing angle and eliminates distortion
- Anti-glare surface treatment
- Case made of durable metal
- Built-in removable desk stand
- Response Time: 16mS
- Built-in VESA 75mm FPMPMI interface for mounting

Resolution: 1440 (H) x 900 (V) dots

Brightness rating: 300 cd/m² (Nit)

Contrast Ratio: 800:1

Display: 19" TFT LCD active matrix

Back Light: Built-in CCFT

Input Signal: Composite NTSC/PAL (*auto switching*),

S-Video, Analog RGB, component

PC compatibility: XGA, SVGA, VGA, MAC II

Dot Pitch: 0.25875 (H) x 0.25875(V)mm

Colors: 6-bit, 262, 144

Number of Pixels: 1,024,00 dots

Viewing angle L/R/T/B: 65/65/50/50

Pixel Configuration: Stripe

Input Signal Level: 1.0V P-P (positive) 75 Ohm

Speakers: 8 ohms, 5 W, 28 x 40mm oval type x 2

Speaker Amplifier: 5 W x 2 @ 10% THD, 100 mV

LCD-1901HD: Dimensions w/o deskstand (WHD): 432.5 x 310 x 44.5mm / 17" x 12.2" x 1.8"

LCD-1901HD: Dimensions w/ deskstand (WHD): 432.5 x 352.5 x 182.8mm / 17" x 13.9" x 7.2"

LCD-1901HDL: Dimensions (WHD): 19-3/8" x 13-5/16" x 2-5/16"

LCD-1901HDR: Dimensions (WHD): 19" x 12.3" x 12.1" (Occupies 7 RU)

Actual visible screen size (WH): 412 x 258mm / 16.2" x 10.1"

Operating temperature: 32~122°F or 0~50°C

Power Requirement: Regulated 12VDC, 3A, negative ground

Part No. DC-1500 required for use in vehicles

Power Consumption: 9.6 W (max)

Includes switching power supply: 100 ~ 240VAC, 47 ~63Hz

Rear Terminal Connections: Composite: BNC video IN/OUT, and

RCA video OUT jack for video 1 or 2

Component: RCA y/Pb/Pr jacks

S-Video IN jack

Audio: 3 RCA IN jacks (composite, audio L/R), and

3.5 stereo audio OUT jack

PC: 15-pin mini D-sub (female)

External IR jack

RS-232: 9-pin

Power: 2.5mm DC IN jack

LCD-1901HD: Weight: Net: 4.5 kg. / 9.85 lbs. Gross: 6.4 kg. / 14.1 lbs.

LCD-1901HDL: Weight: Net: 4.9 kg. / 10.9 lbs. Gross: 6.1 kg. / 13.5 lbs.

LCD-1901HDR: Weight: Net: 4.9 kg. / 10.9 lbs. Gross: 6.1 kg. / 13.5 lbs.

Flush-mounted 19" Monitor

Model LCD-1901HDL (shown above)

Dimensions (WHD): 19-3/8" x 13-5/16" x 2-5/16"

Installers Cut-Out (WH): 18" x 12-1/16"

Rack-mounted 19" Monitor

Model LCD-1901HDR (shown above)

Dimensions (WHD): 19" x 12.3" x 12.1"

Occupies 7 RU

Optional Accessories

HM-400	Under-cabinet hinge mount
WM-30	Wall mount bracket (fixed)
WM-302	Wall mount with swing arm & 4-way adjustable
WMC-1720	Ceiling mount



Schedule

GS-07F-0069L, SIN: 246-42(1), 246-50