

The Biggest Thing in Little LCD Monitors

LCD-501 LCD-501X3



LCD- 501X3
Triple 19" Rack Mount

Active Matrix 5" Color LCD Monitor



LM-BR- 501
Unit in Brass Flush Mount Kit



LCD- 501

- Wide operating power range (10 ~ 30VDC)
- Picture on demand/power saving feature
- Front mounted stereo headphone jack for private listening (no built-in speakers)
- Slim space saving design
- For color and B&W applications
- Compact and light weight for easy installation or mobile use
- Low power consumption
- Case made of durable ABS plastic
- Active matrix technology allows wide viewing angle
- Active matrix technology eliminates distortion
- Front controls for color, brightness and audio volume
- A/C adaptor, Part No. AC-2000, included

Optional Accessories

- BB-5000 Metal bracket for Anton-Bauer battery
 BP-563C Rechargeable 2200mAH battery pack provides approximately 5 hrs. of operation
 DC-12 Car Cord
 DC-12D Dual Car Cord
 HS-1 Hot Shoe mount
 LM-BR-501 Brass Flush Mount Kit (see above)
Requires rear access to install.
 Dimensions (WH): 5.82" x 5.43"
 Installer's cut-out: 5.15"(W) x 4.44"(H)
 MB-1 Desk Stand
 MB-72M Metal Mounting Bracket
 RM-501 EIA Rack Mount Panel, black metal (shown above)
 19"(W) x 5.3"(H) x 0.8"(D) (occupies 3 RU)
 Holds 3 monitors.
 WM-1 Wall mount bracket

- Display: 5" TFT LCD active matrix
 Back Light: CCFT
 Input Signal: NTSC/PAL (auto switching)
 Resolution: 600(H) x 234(V) dots
 Active Area: 102.6(H) x 73.9(V)
 Dot Pitch: 0.171(H) x 0.316(V)
 Brightness rating: 240 cd/m² (Nit)
 Number of Pixels: 140,400
 Contrast Ratio: 120:1
 Viewing angle L/R/T/B: 55°/55°/15°/35°
 Pixel Configuration: Stripe
 Power Requirement: 12VDC (1A, + pin)
 Operating Power Range: 10 ~ 30 VDC
 Power Consumption: 7 W (max.)
 Input Signal Level: 1.0V P-P (positive) 75 Ohm
 Audio Input Level: 1.0V P-P
 Audio output: 0.3 W
 Audio Input Impedance: 10K ohm
 Audio Band Width: 15 KHz
 Dimensions (WHD): 146 x 105 x 30.5mm / 5.7" x 4.1" x 1.2"
 Actual visible screen size(WH): 102 x 74mm / 4" x 2.9"
 Monitor Mounting: Mounting pad with ¼-20 threaded socket
 Operating temperature: 50 ~ 104°F or 10 ~ 40°C, 85% RH max.
 Storage temperature: -4 ~ 140°F or -20 ~ 60°C, 85% RH max.
 DIN Cable Connections: RCA video IN
 RCA right audio IN
 RCA left audio IN
 2.1 DC IN jack
 LCD-501 Weight: Net: 363g / 12.8oz.
 Gross: 1.2 kg. / 2.7 lbs.
 LCD-501X3 Weight: Net: 2.4 kg / 5.3 lbs.
 Gross: Est. 5.3 kg. / 11.8 lbs.

GSA Schedule For LCD-501X3 only.
 GS-07F-0069L, SIN: 246-42(1), 246-50