

# 8.4" PC- capable LCD Monitors

LCD-840V

LCD-840VL



LCD-840VL



LCD-840V

- Durable steel case
- Composite, S-Video, and PC capability
- Response Time: 20ms/30ms (rising/falling)
- Wireless remote control
- Active matrix technology allows wide viewing angle and eliminates distortion
- For color and B/W applications
- A/C adaptor included
- Built-in interface for wall or arm mounting  
VESA 75mm FPMPMI compliant

Display: 8.4" TFT LCD active matrix  
Input Signal: NTSC/PAL(auto sensing), S-Video, Analog RGB  
Resolution: 800(H) x 600(V) dots  
Brightness rating: 150 cd/m<sup>2</sup>(Nit)  
Contrast Ratio: 200:1  
Viewing angle L/R/T/B: 45/45/35/15  
Power Requirements: Regulated 12 VDC, 3A (LCD-641V: Regulated 12 VDC, 2A)  
Power Consumption: 30 W (max)  
Video Input Level: 1.0 V P-P (positive) 75 Ohm

LCD-840V: Dimensions (WHD): 264 x 163 x 38mm / 10.4" x 6.4" x 1.5"  
LCD-840VL: Dimensions (WHD): 290 x 213 x 40.6mm / 11.4" x 8.4" x 1.6"  
Actual visible screen size (WH): 174 x 131mm / 6.9" x 5.2"  
Operating temperature: 50 ~ 104°F or 10 ~ 40°C

Connections: Composite: RCA video IN, BNC video IN/OUT  
S-Video IN  
PC: 15-pin mini D-sub (female)  
Power: 2.1 DC IN jacks  
LCD-840V: Weight: Net: 3.2 kg. / 5.4 lbs.  
Gross: 3.6 kg. / 8 lbs.  
LCD-840VL: Weight: Net: Est. 2.9 kg. / 6.4 lbs.  
Gross: 4.1 kg. / 9 lbs.

## 8" Flush-mounted LCD Monitor Model LCD-840VL (shown above)

Dimensions (WHD): 290 x 213 x 40.6mm / 11.4" x 8.4" x 1.6"  
Installer's Cut-out (WH): 229 x 175mm / 9" x 6.9"  
Weight: Net: Est. 2.9 kg. / 6.4 lbs. Gross: 4.1 kg. / 9 lbs.

## Optional Accessories for LCD-840V

MB-3 Desk stand  
HM-400 Under-cabinet hinge mount